

SI8515

Octal RS-232

IndustryPack®



Product Description

The Newwood Solutions IP-SI-8515 is a single-width Industry Pack that provides 8 serial interface lines with the following characteristics:-

- 8 independent RS-232 UART channels
- 64 byte Transmit and Receive FIFOs
- Transmit and Receive FIFO level counters
- Programmable Tx and Rx FIFO Trigger Levels
- Automatic RTS/CTS Flow Control
- Automatic Xon/Xoff Software Flow Control with Status Indication
- Programmable Data Rate with Prescaler
- Up to 6.25 Mbps Serial Data Rate
- Single Interrupt Output for all 8 UARTs
- Global Interrupt Source for all 8 UARTs
- Simultaneous UART channel initialisation

Product Specifications

Size: Single width Industry Pack 1.8ins x 3.9 ins

Operating temp: 0 to 45 deg C ambient

Number of channels: 8

Max. baud rate: 921.6kbps with internal clock.

Data format: Binary/ASCII Input/Output levels: RS-232

Internal clock: 14.7456MHz oscillator Clock accuracy: +/-100ppm (0.01%)
Power: +5V @ 400mA typical

Fuses: F1 1A – connects +12V to I/O connector

F2 1A – connects –12V (not used)

Jumpers: J1 Boot jumper allows FPGA to load.

J2, J3 not used.

